

## SONOREX SUPER ultrasonic bath 3 litres, heatable



SONOREX SUPER baths with 0.9 to 90.0 litres capacity.

The robust and compact SONOREX SUPER ultrasonic baths are characterised by their convenient operability. The size and number of cleaning products or sample vessels determine the selection of the appropriate ultrasonic cleaning bath.

- Heating power: 140 Watt
- External dimensions (L x W x H mm): 260  $\times$  160  $\times$  250 mm
- Internal dimensions of oscillating tank (L x W x D mm): 240  $\times$  140  $\times$  100 mm
- Vibration systems
- Ultrasonic frequency 35 kHz
- Time setting 1 15 min,  $\pm$  5 %, continuous operation ( $\infty$ )
- H types with adjustable temperature range 30 80 °C, RK 31 H with heater 65 °C fixed setting Oscillating tanks made of stainless steel

• RK 102 H with hard-chrome plated oscillating tank, robust stainless steel housing - easy to clean and protected against dripping water

• from RK 102 H the ultrasonic baths have a drain for easy emptying

Products for the electronic industry





- Operating voltage 230 V  $^{\sim}$  (±10 %), alternatively 115 V  $^{\sim}$  (±10 %), 50/60 Hz

• SONOREX SUPER ... CH ultrasonic baths from 45 to 90 litres capacity offer an even

longer lifetime due to welded oscillating tank made of stainless steel 1.4404, 2 mm

• SONOREX SUPER ultrasonic baths: medical device class I

item number	WL10490
model	RK 100 H
manufacturer	BANDELIN
manufacturer item number	312
order unit	1 piece
content unit	1 piece
content in liter	31
nominal power	80 W
Power consumption	1 AMPERE
max. ultrasonic power	320 W

Products for the electronic industry

