

## SONOREX SUPER ultrasonic bath 9.0 litres, heatable



SONOREX SUPER baths with 0.9 to 90.0 litres capacity.

The robust and compact SONOREX SUPER ultrasonic baths are characterized by their comfortable operability. The size and number of cleaning products or sample vessels determine the selection of the appropriate ultrasonic cleaning bath.

- Heating power: 600 Watt
- External dimensions (L x W x H mm): 530 × 165 × 300 mm
- Internal dimensions of oscillating tank (L x W x D mm): 500 × 140 × 150 mm
- Vibration systems
- Ultrasonic frequency 35 kHz
- Time setting 1 - 15 min, ± 5 %, continuous operation (∞)
- H types with adjustable temperature range 30 - 80 °C, RK 31 H with heater 65 °C - fixed setting
- Vibration troughs made of stainless steel
- RK 102 H with hard-chrome plated oscillating tank, robust stainless steel housing - easy to clean and protected against dripping water
- from RK 102 H the ultrasonic baths have a drain for easy emptying

Products for the electronic industry



- Operating voltage 230 V<sup>~</sup> (±10 %), alternatively 115 V<sup>~</sup> (±10 %), 50/60 Hz
- SONOREX SUPER ... CH ultrasonic baths from 45 to 90 litres capacity offer an even longer lifetime due to welded oscillating tank made of stainless steel 1.4404, 2 mm
- SONOREX SUPER ultrasonic baths: medical device class I

item number	WL10493
model	RK 156 BH
manufacturer	BANDELIN
manufacturer item number	646
order unit	1 piece
content unit	1 piece
content in liter	9 l
nominal power	215 W
Power consumption	3,6 AMPERE
max. ultrasonic power	860 W