

## ESD PCB magazine 704.1, polysyrol, 400 x 460 x 563 mm

---



PCB magazines series 700: variable width adjustment by toothed belt by hand

Safety screw

Clamping of the toothed belt by a knurled screw prevents accidental adjustment of the movable side wall.

Four precision spindles

for adjusting the movable side wall

Transport lock

A latch is mounted on the front and rear as standard. When lifted, the latch is moved outwards and locks in the upper position. The PCBs can be inserted or removed. When lifted again, the guides are locked.

Toothed belt

By pulling the toothed belt, the web walls are adjusted to the required PCB width.

- ESD PCB magazine partially assembled
- Model: 704.1
- LP: W = 10-330 mm (adjustable), L max = 447 mm

---

Products for the electronic industry



- Magazine: H x W x D = 563 x 400 x 460 mm
- groove depth 3 mm, with transport lock
- Plastic web wall
- width adjustment by toothed belt
- stackable (with stacking knobs) or for reversible operation

<b>item number</b>	<b>WL10778</b>
model	8917704
manufacturer	CAB
manufacturer item number	8917704
GPSR manufacturer information	CAB Produkttechnik Wilhelm-Schickard-Straße 14 DE-76131 Karlsruhe www.cabgmbh.com
order unit	1 piece
content unit	1 piece
temperature max.	60 °C
ESD safe	yes
Series PCB magazines	Series 700
Material PCB magazine	plastic