

Xonic ESD Screwdriver slotted, 2.5 x 60 mm, 157 mm



- Ergonomically designed handle with rotating trough cap for optimum control of the rotary movement even at lowest torques
- High quality chrome-vanadium steel shaft for exceptional strength and durability
- Precisely fitting tips for exact adjustments and damage-free screwing in
- Black blades, not chrome-plated, avoid reflections and flaking of chrome particles
- Fully ESD compliant, dissipative in all areas
- Size: 2,5 mm
- Visible blade length: 60 mm
- total length: 157 mm

Item no.	WL11141
Model	4880X-ESD-2,5x60
Manufacturer	C.K
Manufacturer article no.	T4880XES256
GPSR manufacturer data	Carl Kammerling International Bendahler Straße 110 DE-42285 Wuppertal www.ck-tools.com
Width	17 mm
Height	17 mm
Length with packaging	207 mm
Width with packaging	17 mm
Height with packaging	17 mm
Sales unit	1 piece
Content unit	1 piece
VDE	no
Screw type	slot
ESD compliant	yes
Packaging dimensions	piece

Products for the electronic industry



Screwdriver type normal screwdrivers

Tool length 157 mm

Applications (screwdriver) slotted screws

Blade width 2.5 mm

Blade thickness 0.4 mm

Other versions

Item no.	Tool length	Blade width	Blade thickness
WL11137	157 mm	0.8 mm	0.2 mm
WL11138	157 mm	1.2 mm	0.25 mm
WL11139	157 mm	1.5 mm	0.3 mm
WL11140	157 mm	1.8 mm	0.3 mm
WL11141	157 mm	2.5 mm	0.4 mm
WL11142	172 mm	2.5 mm	0.4 mm
WL11143	197 mm	3 mm	0.5 mm
WL11146	197 mm	4 mm	0.6 mm
WL11144	250 mm	3 mm	0.5 mm