

Xonic ESD screwdriver slot, 2.5 x 75 mm, 172 mm



- Ergonomically designed handle with rotating trough cap for optimum control of the rotary movement even at lowest torques
- High quality chrome-vanadium steel shaft for exceptional strength and durability
- Precisely fitting tips for exact adjustments and damage-free screwing in
- Black blades, not chrome-plated, avoid reflections and flaking of chrome particles
- Fully ESD compliant, dissipative in all areas
- Size: 2,5 mm
- Visible blade length: 75 mm
- total length: 172 mm

Item no.	WL11142
Model	4880X-ESD-2,5x75
Manufacturer	C.K
Manufacturer article no.	T4880XES257
GPSR manufacturer data	Carl Kammerling International Bendahler Straße 110 DE-42285 Wuppertal www.ck-tools.com
Width	17 mm
Height	17 mm
Length with packaging	220 mm
Width with packaging	17 mm
Height with packaging	17 mm
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
VDE	no
Screw type	slot
ESD compliant	yes

Products for the electronic industry



Packaging dimensions	piece
Screwdriver type	normal screwdrivers
Tool length	172 mm
Applications (screwdriver)	slotted screws
Blade width	2.5 mm
Blade thickness	0.4 mm

Other versions

Item no.	Tool length	Blade width	Blade thickness
WL11137	157 mm	0.8 mm	0.2 mm
WL11138	157 mm	1.2 mm	0.25 mm
WL11139	157 mm	1.5 mm	0.3 mm
WL11140	157 mm	1.8 mm	0.3 mm
WL11141	157 mm	2.5 mm	0.4 mm
WL11142	172 mm	2.5 mm	0.4 mm
WL11143	197 mm	3 mm	0.5 mm
WL11146	197 mm	4 mm	0.6 mm
WL11144	250 mm	3 mm	0.5 mm