

Dispensing needle 0.5", 45° angled, gauge 20, pink, curved



Curved Optimum® stainless steel tips with SafetyLok™ holders are available with 45° and 90° bends. They enable precise and repeatable material dosing even in difficult applications.

Dispensing needle for cartridge

- 45° angled
- Capillary L = 1/2"
- D inside = GA 20 (0.58-0.62 mm), pink
- Capillary passivated stainless steel
- Polypropylene receptacle with Luer-Lock thread
- inner diameter: 0.61 mm

Item no.

WL11703

Products for the electronic industry



Model	5120-45-B / 7018179
Manufacturer	NORDSON EFD
Manufacturer article no.	7018179
GPSR manufacturer data	Nordson Deutschland GmbH Kapellenstraße 12 DE-85622 Feldkirchen www.nordson.com
Sales unit	1 piece
Content unit	1 piece
Colour	pink
Incl. battery	no
Gauge	GA 20
Angle of the dispensing needle	45 °
Capillary length (inch)	0.5 in
Tip type (dispensing needles)	angled tip
Inner diameter	0.61 mm
Outer diameter	0.91 mm
Tip shape	bent
ESD compliant	no

Other versions

Item no.	Angle of the dispensing needle
WL11703	45 °
WL28587	90 °