

## Electronic-Super-Knips® , side cutter for fiberglass, 125 mm



Electronic Super Knips® precision pliers for the finest cutting work, e.g. in electronics and precision mechanics. Ground, very sharp cutting edges without facet. Exactly shaped tips also cut adjacent wires from  $\varnothing$  0.2 mm. Shear cut with controlled micro cutting edge offset for long life and ultra-precise cutting of even the thinnest wires. Joint with stainless steel rivet. Extremely smooth action for fatigue-free work. With opening spring and opening limiter. Also suitable for cutting fibre optic cables (optical fibres). Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC. Special tool steel, multi-stage oil-hardened. - Shape: 6 - Cutting values medium hard wire (diameter):  $\varnothing$  1,2mm - Cutting values soft wire (diameter):  $\varnothing$  0,2 - 1,6mm - Jaw length (B): 9mm - Jaw thickness (at joint) (D): 7,5mm - Head width (A): 13,5mm

- Precision pliers for finest cutting work, e.g. in electronics and precision mechanics
- Ground, very sharp cutting edges without facet
- Exactly shaped tips also cut adjacent wires from  $\varnothing$  0.2 mm
- Shear cut with controlled micro cutting edge offset for long service life and ultra-precise cutting of even the thinnest wires
- Joint with stainless steel rivet
- Extremely smooth action for fatigue-free work
- With opening spring and opening limiter

Item no.	WL13362
Model	78 61 125
Manufacturer	KNIPEX
Manufacturer article no.	78 61 125
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg

www.knipex.de

Length	130 mm
Width	62 mm
Height	13 mm
Length with packaging	189 mm
Width with packaging	72 mm
Height with packaging	48 mm
Volume with packaging	0.64 dm <sup>3</sup>
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Standards	DIN ISO 9654
Product series	Electronic-Super-Knips®
RoHS compliant	no
Surface	burnished
VDE	no
Cut shape	without bevel
ESD compliant	no
Tool length	125 mm
Type of side cutters	side cutter
Grip (expression)	With multi-component sheaths
Cutting value wire diameter (medium)	1.2 mm
Cutting value wire diameter (soft)	1.6 mm
Type of pliers	cutting pliers