

## ESD desoldering braid Pro-Wick®, 1.4 mm, yellow, 1.5 m

---



For fast and efficient cleaning, the 1809-5F desoldering braid with a width of 1.4 mm, wetted with Rosin flux, is ideal for the production/repair of printed circuit boards in large quantities. The desoldering braid is a flux wetted copper braid that is used to remove solder so that components can be replaced and excess solder removed. The soldering iron is placed on the braid - as soon as both have been brought to the correct temperature, the flux is activated. The capillary action of the braid draws the solder up the wire. Techspray desoldering braids are available on ESD-safe spools and are therefore suitable for use with ESD-sensitive components.

- Braid coated with rosin
- Highest absorption capacity
- Complies with MIL-F-14256, Type R
- ESD compliant

Item no.

WL15055

---

Products for the electronic industry



Model	1809-5F
Manufacturer	TECHSPRAY
Manufacturer article no.	1809-5F
GPSR manufacturer data	TECHSPRAY ITW Saffierlaan 5 NL-2132 Hoofddorp www.techsprayeu.com
Length	1500 mm
Width	1.4 mm
Sales unit	1 rolls
Content unit	1 rolls
Colour	yellow
Colour	yellow
Standards	MIL-F-14256; NASA NHB 5300, 4 (34-1); NASA NPC 200-4; NASA SP5002; 1821: HP 8690-0588; 1823: HP 8690-0577; IPC Standard-J-STD-004
RoHS compliant	yes
ESD compliant	yes

## Other versions

Item no.	Width	Length
WL15046	0.9 mm	3000 mm
<b>WL15055</b>	<b>1.4 mm</b>	<b>1500 mm</b>
WL15052	1.4 mm	3000 mm
WL15060	1.9 mm	1500 mm
WL15057	1.9 mm	3000 mm
WL15058	1.9 mm	30500 mm
WL15064	2.5 mm	1500 mm
WL15061	2.5 mm	3000 mm
WL15062	2.5 mm	30500 mm