

side cutters, 80 series, pointed jaws, fine bevel, 0.3-2 mm



Side cutters with pointed jaws, e.g. for assembly work in confined spaces.

Made of high-performance ball bearing steel, burnished. Cutting and jaws computer-ground, thus highest precision and constant quality. Induction hardening of the cutting edges to 63-65 HRC. With plastic handles and opening spring.

- Cutting capacity copper D = 0.3-2 mm

Article no.	WL16040
Model	8164
Manufacturer	LINDSTRÖM
Manufacturer article no.	8164
GPSR manufacturer data	SNA Europe SAS/ LINDSTRÖM Antigua Carretera Altube km 5.5 ES-01006 Vitoria-Gasteiz www.lindstromtools.com
Length	165 mm
Width	100 mm
Height	75 mm
Sales unit	1 piece

Products for the electronic industry



Content unit	1 piece
Product series	80 series
VDE	no
Head width	16 mm
Jaw shape	pointed
Cut shape	small bevel
ESD compliant	no
Side cutter cutting capacity	0,3 - 2 mm
Cutting edge type	with fine bevel
Jaw shape	pointed
Tool length	125 mm
Type of side cutters	side cutter
Length of the jaws	16 mm

Other versions

Article no.	Side cutter cutting capacity	Cutting edge type	Jaw shape
WL70870	0,1 - 0,5 mm	without bevel	pointed
WL16016	0,1 - 0,6 mm	with fine bevel	pointed
WL15994	0,1 - 0,8 mm	without bevel	oval
WL16014	0,1 - 0,8 mm	without bevel	sharpened to a point
WL15992	0,1 - 1 mm	with fine bevel	oval
WL16012	0,1 - 1 mm	with fine bevel	sharpened to a point
WL16002	0,1 - 1 mm	without bevel	oval
WL16008	0,1 - 1 mm	without bevel	pointed
WL16000	0,1 - 1,25 mm	with fine bevel	oval
WL16023	0,1 - 1,25 mm	without bevel	oval
WL15990	0,2 - 1 mm	with bevel	oval
WL16010	0,2 - 1 mm	with bevel	sharpened to a point
WL16031	0,2 - 1 mm	without bevel	sharpened to a point
WL16020	0,2 - 1,6 mm	with fine bevel	oval
WL16027	0,2 - 1,6 mm	with fine bevel	pointed
WL16006	0,2 - 1,25 mm	with fine bevel	pointed
WL16030	0,2 - 1,25 mm	with fine bevel	sharpened to a point

Products for the electronic industry



WL15997	0,2 - 1,25 mm	with bevel	oval
WL16004	0,2 - 1,25 mm	with bevel	pointed
WL20703	0,2 - 1,25 mm	without bevel	pointed
WL70872	0,3 - 1,5 mm	with fine bevel	pointed
WL16018	0,3 - 1,6 mm	with bevel	oval
WL16025	0,3 - 1,6 mm	with bevel	pointed
WL16036	0,3 - 1,6 mm	without bevel	oval
WL16041	0,3 - 1,6 mm	without bevel	pointed
WL20704	0,3 - 1,25 mm	with bevel	sharpened to a point
WL70873	0,3 - 1,25 mm	without bevel	pointed
WL16034	0,3 - 2 mm	with fine bevel	oval
WL16040	0,3 - 2 mm	with fine bevel	pointed
WL70871	0,4 - 1,5 mm	with bevel	pointed
WL16032	0,4 - 2 mm	with bevel	oval
WL16037	0,4 - 2 mm	with bevel	pointed
WL20702	0,5 mm	with cutting edge and bevel	oval