

## ERGO™ Insulated screwdriver for slotted screws with 3-component handle, VDE-certified 0.4 mm x 2.5 mm x 75 mm



- Developed as part of the ERGO™ process
- Insulated ERGO™ Screwdrivers for slotted screws
- Burnished tip for higher accuracy
- Three-component handle for maximum ease of use, soft material with ribbed surface for better grip and greater power transmission
- Flat side parts prevent rolling away
- Integrated suspension eye
- The correct blade can be easily identified by the colour marking and the symbol on the end of the handle
- No colour identification in extra small handle, small sizes from 2.5 to 3.5
- High performance steel alloy, the insulation layer is sprayed directly onto the blade
- For work on live workpieces, up to 1000 V
- Individually tested and manufactured according to IEC 60900, tested in a water bath at 10000 V
- Standards: ISO 2380/DIN 5264

|              |          |
|--------------|----------|
| item number  | WL16076  |
| model        | BE 8010S |
| manufacturer | BAHCO    |

Products for the electronic industry



|                               |   |
|-------------------------------|---|
| manufacturer item number      | BE-8010S  |
| GPSR manufacturer information | BAHCO Werkzeuge<br>Maybachstr. 10<br>DE-71711 Steinheim<br>www.bahco-werkzeuge.de |
| length                        | 270 mm  |
| width                         | 60 mm   |
| height                        | 40 mm   |
| order unit                    | 1 piece   |
| content unit                  | 1 piece   |
| handle length                 | 122 mm  |
| VDE                           | yes   |
| type of screw                 | slot  |
| ESD safe                      | no  |
| packaging mass                | piece   |
| type of screwdriver           | 1000 V insulated  |
| Blade thickness               | 0.4 mm  |
| Handle width                  | 17 mm   |
| tool length                   | 197 mm  |
| handle diameter               | 17 mm   |
| blade length                  | 2.5 mm  |
| blade width                   | 2.5 mm  |

## Other versions

| item number    | blade length  | blade width & Blade thickness |
|----------------|---------------|-------------------------------|
| <b>WL16076</b> | <b>2.5 mm</b> | <b>2.5 mm &amp; 0.4 mm</b>    |
| WL16088        | 2.9 mm        | 3 mm & 0.5 mm                 |
| WL18286        | 3.43 mm       | 3.5 mm & 0.6 mm               |
| WL16081        | 100 mm        | 4 mm & 0.8 mm                 |
| WL16082        | 125 mm        | 5.5 mm & 1 mm                 |
| WL53690        | 150 mm        | 6.5 mm & 1.2 mm               |
| WL21092        | 175 mm        | 8 mm & 1.2 mm                 |
| WL53456        | 200 mm        | 10 mm & 1.6 mm                |
| WL53458        | 200 mm        | 12 mm & 2 mm                  |