

ERGO™ Insulated screwdriver for slotted screws with 3-component handle, VDE-certified 0.8 mm x 4 mm x 100 mm



- Developed as part of the ERGO™ process
- Insulated ERGO™ Screwdrivers for slotted screws
- Burnished tip for higher accuracy
- Three-component handle for maximum ease of use, soft material with ribbed surface for better grip and greater power transmission
- Flat side parts prevent rolling away
- Integrated suspension eye
- The correct blade can be easily identified by the colour marking and the symbol on the end of the handle
- No colour identification in extra small handle, small sizes from 2.5 to 3.5
- High performance steel alloy, the insulation layer is sprayed directly onto the blade
- For work on live workpieces, up to 1000 V
- Individually tested and manufactured according to IEC 60900, tested in a water bath at 10000 V
- Standards: ISO 2380/DIN 5264

item number	WL16081
model	BE 8040S
manufacturer	BAHCO

Products for the electronic industry



manufacturer item number	BE-8040S
length	270 mm
width	60 mm
height	40 mm
order unit	1 piece
content unit	1 piece
handle length	122 mm
VDE	yes
type of screw	slot
ESD safe	no
packaging mass	piece
type of screwdriver	1000 V insulated
Blade thickness	0.8 mm
Handle width	17 mm
tool length	222 mm
handle diameter	17 mm
blade length	100 mm
blade width	4 mm

Other versions

item number	blade length	blade width & Blade thickness
WL16076	2.5 mm	2.5 mm & 0.4 mm
WL16088	2.9 mm	3 mm & 0.5 mm
WL18286	3.43 mm	3.5 mm & 0.6 mm
WL16081	100 mm	4 mm & 0.8 mm
WL16082	125 mm	5.5 mm & 1 mm
WL53690	150 mm	6.5 mm & 1.2 mm
WL21092	175 mm	8 mm & 1.2 mm
WL53456	200 mm	10 mm & 1.6 mm
WL53458	200 mm	12 mm & 2 mm