

ERGO™ Screwdriver for slotted screws, straight, with 3-component handle, 0.4 mm × 2.5 mm × 75 mm



- Screwdriver developed in the course of the ERGO™ process
- For slotted screws
- Burnished tip for greater accuracy
- 3-component handle for maximum ease of use, soft material with rigid surface provides comfortable grip and better power transmission
- Maximum comfort with minimum effort due to ergonomic design
- The correct blade can be easily identified by the colour marking and the symbol on the end of the handle
- No colour identification in extra small handle, small sizes from 2 to 3.5
- Flat sides prevent rolling away
- integrated suspension opening
- High performance steel alloy blade, chrome plated and fully hardened for maximum corrosion protection and long life
- Standards: ISO 2380 and DIN 5264

Item no.	WL16086
Model	BE 8210
Manufacturer	BAHCO
Manufacturer article no.	BE-8210
GPSR manufacturer data	BAHCO Werkzeuge Maybachstr. 10 DE-71711 Steinheim www.bahco-werkzeuge.de

Length	270 mm
Width	60 mm
Height	43 mm
Sales unit	1 piece
Content unit	1 piece
Handle length	122 mm
VDE	no
Screw type	slot
ESD compliant	no
Packaging dimensions	piece
Screwdriver type	normal screwdrivers
Blade thickness	0.4 mm
Handle width	17 mm
Tool length	197 mm
Handle diameter	17 mm
Blade length	75 mm
Blade width	2.5 mm
Blade thickness	0.4 mm

Other versions

Item no.	Blade length	Blade thickness	Blade width
WL53430	60 mm	0.3 mm	2 mm
WL16075	60 mm	0.4 mm	2.5 mm
WL16077	60 mm	0.5 mm	3 mm
WL16086	75 mm	0.4 mm	2.5 mm
WL16078	75 mm	0.5 mm	3 mm
WL16079	75 mm	0.6 mm	3.5 mm
WL53432	100 mm	0.5 mm	3 mm
WL16080	100 mm	0.8 mm	4 mm
WL16087	125 mm	0.5 mm	3 mm
WL16089	125 mm	0.6 mm	3.5 mm
WL53450	125 mm	1 mm	5.5 mm
WL53688	150 mm	1 mm	5.5 mm

WL53452	150 mm	1 mm	6 mm
WL53689	150 mm	1.2 mm	6.5 mm
WL16090	175 mm	0.8 mm	4 mm
WL19948	175 mm	1.6 mm	8 mm
WL53447	200 mm	0.5 mm	3 mm
WL53449	200 mm	0.6 mm	3.5 mm
WL20734	200 mm	1 mm	5.5 mm

