

## ERGO™ Screwdriver for slotted screws with hexagon shaft and attachment, with 3-component handle, 1.6 mm × 8 mm × 175 mm



- Screwdriver developed in the course of the ERGO™ process
- With hexagon head for slotted screws
- Burnished tip for greater accuracy
- 3-component handle for maximum ease of use, soft material with rigid surface provides comfortable grip and better power transmission
- Maximum comfort with minimum effort due to ergonomic design
- The correct blade can be easily identified by the colour marking and the symbol on the end of the handle
- Flat sides prevent rolling away
- integrated suspension opening
- Hexagonal shaft and attachment for rotation support with wrench
- High performance steel alloy blade, chrome plated and fully hardened for maximum corrosion protection and long life
- Standards: ISO 2380 and DIN 5264

|                               |   |
|-------------------------------|---|
| item number                   | WL16118   |
| model                         | BE 8865   |
| manufacturer                  | BAHCO   |
| manufacturer item number      | BE-8865   |
| GPSR manufacturer information | BAHCO Werkzeuge<br>Maybachstr. 10<br>DE-71711 Steinheim |

www.bahco-werkzeuge.de

|                     |                     |
|---------------------|---------------------|
| length              | 370 mm              |
| width               | 120 mm              |
| height              | 40 mm               |
| order unit          | 1 piece             |
| content unit        | 1 piece             |
| handle length       | 161 mm              |
| VDE                 | no                  |
| type of screw       | slot, hexagonal     |
| ESD safe            | no                  |
| packaging mass      | piece               |
| type of screwdriver | normal screwdrivers |
| Blade thickness     | 1.6 mm              |
| Handle width        | 36 mm               |
| tool length         | 336 mm              |
| handle diameter     | 36 mm               |
| blade length        | 175 mm              |
| blade width         | 8 mm                |
| blade thickness     | 1.6 mm              |

## Other versions

| item number    | blade length  | blade thickness | blade width |
|----------------|---------------|-----------------|-------------|
| WL53686        | 125 mm        | 1 mm            | 5.5 mm      |
| WL16085        | 125 mm        | 1.6 mm          | 8 mm        |
| WL53687        | 150 mm        | 1.2 mm          | 6.5 mm      |
| <b>WL16118</b> | <b>175 mm</b> | <b>1.6 mm</b>   | <b>8 mm</b> |
| WL16119        | 175 mm        | 1.6 mm          | 10 mm       |
| WL16120        | 200 mm        | 2 mm            | 2 mm        |
| WL16121        | 200 mm        | 2.5 mm          | 2.5 mm      |