

## ERGO™ Insulated screwdriver for Phillips screws with 3-component handle, VDE-certified PH4 x 36 mm x 200 mm



- Developed as part of the ERGO™ process
- Insulated ERGO™ VDE Screwdrivers for cross-heads
- Burnished tip for higher accuracy
- Three-component handle for maximum ease of use, soft material with ribbed surface for better grip and greater power transmission
- Maximum comfort and minimum stress thanks to the ergonomic design
- Colour marking at the end of the handle for quick identification of the blade type
- The correct blade can be easily identified by the colour marking and the symbol on the end of the handle
- No colour identification in extra small handle, size PH0
- Flat side parts prevent rolling away
- Integrated suspension eye
- Flat side parts prevent rolling away
- Standards: ISO 8764/DIN 5260, IEC 60900, VDE certified
- Blade made of high-performance steel alloy
- For work on live workpieces, up to 1000 V
- High-quality insulation layer, which is sprayed directly onto the blade
- Individually tested and manufactured according to IEC 60900, tested in a water bath at 10000 V
- The correct tip can easily be identified by the colour marking on the handle

item number

WL18291

Products for the electronic industry



model	BE 8640S
manufacturer	BAHCO
manufacturer item number	BE-8640S
length	370 mm
width	122 mm
height	40 mm
order unit	1 piece
content unit	1 piece
handle length	161 mm
VDE	yes
type of screw	PH4
ESD safe	no
packaging mass	piece
type of screwdriver	1000 V insulated
Handle width	36 mm
tool length	361 mm
handle diameter	36 mm
blade length	200 mm

## Other versions

item number	type of screw	blade length	Handle width	tool length
WL18287	PH0	75 mm	17 mm	197 mm
WL18288	PH1	80 mm	27 mm	202 mm
WL53474	PH1	150 mm	27 mm	272 mm
WL53478	PH2	100 mm	27 mm	222 mm
WL18289	PH2	100 mm	36 mm	222 mm
WL53480	PH2	175 mm	36 mm	297 mm
WL18290	PH3	150 mm	36 mm	272 mm
<b>WL18291</b>	<b>PH4</b>	<b>200 mm</b>	<b>36 mm</b>	<b>361 mm</b>