

side cutter, ergo, 160 mm, unpacked



- Side cutter, which was developed in the course of the ERGO™ process
- ISO 5749
- Finish: burnished, rust protection treated
- Material: high-performance steel alloy, ERGO™ handles with 2-component material, thermoplastic surface on hard polypropylene for optimum grip
- Induction-hardened cutting edges
- Progressive cutting: the cutting radius runs along the edges to cut hard materials like piano wire close to the joint and soft materials like copper and plastic insulated wires at the tip
- Bolted connection that ensures excellent cutting performance and accuracy of fit of the cutting edges
- Distance between joint and cutting edge reduced for maximum cutting capacity with small opening width of the handle
- Slim, rounded jaws for improved access to hard-to-reach areas
- Patented opening spring integrated in the handle with on/off function
- IP = Industrial packaging

| | |
|--------------------------|-------------|
| item number | WL18333 |
| model | 2101G-160IP |
| manufacturer | BAHCO |
| manufacturer item number | 2101G-160IP |
| length | 160 mm |

Products for the electronic industry



| | |
|------------------------------|--|
| width | 58 mm |
| order unit | 1 piece |
| content unit | 1 piece |
| total length | 160 mm |
| VDE | no |
| head width | 21 mm |
| ESD safe | no |
| tool length | 160 mm |
| type of side cutter | side cutter |
| description cutting capacity | piano wire cutting capacity D max = 2 mm |
| length of jaws | 18 mm |

Other versions

| item number | length | head width |
|----------------|---------------|--------------|
| WL17958 | 125 mm | 17 mm |
| WL17904 | 140 mm | 19 mm |
| WL18333 | 160 mm | 21 mm |
| WL21178 | 180 mm | 23 mm |