

Dosing needle 0.5", 45° angled, gauge 15, amber, curved



Curved Optimum® stainless steel tips with SafetyLok™ holders are available with 45° and 90° bends. They enable precise and repeatable material dosing even in difficult applications.

Dispensing needle for cartridge

- 45° angled
- Capillary L = 1/2"
- D inside = GA 15 (1,33-1,38 mm), amber
- Capillary passivated stainless steel
- Polypropylene receptacle with Luer-Lock thread
- inner diameter: 1.36 mm

Item no.

WL18576

Products for the electronic industry



| | |
|--------------------------------|--|
| Model | 5115-45-B / 7018069 |
| Manufacturer | NORDSON EFD |
| Manufacturer article no. | 7018069 |
| GPSR manufacturer data | Nordson Deutschland GmbH Kapellenstraße 12 DE-85622 Feldkirchen www.nordson.com |
| Sales unit | 1 piece |
| Content unit | 1 piece |
| Colour | amber |
| Incl. battery | no |
| Gauge | GA 15 |
| Angle of the dispensing needle | 45 ° |
| Capillary length (inch) | 0.5 in |
| Tip type (dispensing needles) | angled tip |
| Inner diameter | 1.36 mm |
| Outer diameter | 1.65 mm |
| Tip shape | bent |
| ESD compliant | no |