

## 800/4 Z Screwdriver bit, slotted, 1.0 x 5.5 mm, 89 mm



With the 800/4 Z screwdriver bit, slotted, 1.0 x 5.5 mm, 89 mm, Wera provides a precisely manufactured solution for slotted screw fastenings at a high quality level. A central feature is For slotted screws, which is particularly advantageous in continuous use. The tool combines durability with high dimensional accuracy - a combination that professionals rely on.

- For slotted screws
- Tough-hard, for universal use
- 1/4" hexagon drive
- Suitable for AEG, ARO, Atlas-Copco, Biax, Black & Decker, Bosch, Buckeye Tools etc.
- Prevents premature breakage of the output tip

Item no.	WL19121
Model	800/4 Z
Manufacturer	WERA
Manufacturer article no.	05059488001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	89 mm
Width	7 mm
Height	7 mm
Length with packaging	118 mm
Width with packaging	35 mm
Height with packaging	15 mm
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
Bit length	89 mm
VDE	no

Products for the electronic industry



Screw type	slot
ESD compliant	no
Tool length	89 mm
Blade length	89 mm
Blade width	5.5 mm
Blade thickness	1 mm

## Other versions

Item no.	Blade width	Blade thickness	Bit length
WL51597	3 mm	0.5 mm	50 mm
WL22853	3 mm	0.5 mm	70 mm
WL22854	3.5 mm	0.6 mm	70 mm
WL89760	3.5 mm	0.6 mm	152 mm
WL89752	4 mm	0.5 mm	50 mm
WL71953	4 mm	0.8 mm	50 mm
WL89764	4 mm	0.8 mm	70 mm
WL73439	4 mm	0.8 mm	89 mm
WL89761	4 mm	0.8 mm	152 mm
WL89753	4.5 mm	0.6 mm	50 mm
WL71800	4.5 mm	0.6 mm	89 mm
WL89754	5.5 mm	0.8 mm	50 mm
WL89755	5.5 mm	1 mm	50 mm
WL89765	5.5 mm	1 mm	70 mm
<b>WL19121</b>	<b>5.5 mm</b>	<b>1 mm</b>	<b>89 mm</b>
WL89762	5.5 mm	1 mm	152 mm
WL89756	6 mm	1 mm	50 mm
WL89757	6.5 mm	1.2 mm	50 mm
WL89766	6.5 mm	1.2 mm	70 mm
WL71801	6.5 mm	1.2 mm	89 mm
WL89763	6.5 mm	1.2 mm	152 mm
WL89758	8 mm	1.2 mm	50 mm
WL71802	8 mm	1.2 mm	89 mm
WL89759	8 mm	1.6 mm	50 mm

WL89767

8 mm

1.6 mm

89 mm

