

ESD Electronic-Super-Knips®, side cutter, fine, with wire clip, 125 mm



Electronic Super Knips® ESD precision pliers for the finest cutting work, e.g. in electronics and precision mechanics. Handles electrically conductive - dissipative. Ground, very sharp cutting edges without facet. Shear cut with controlled micro cutting edge offset for long life and ultra-precise cutting of even the thinnest wires. Precisely shaped tips also cut adjacent wires from $\varnothing 0.2$ mm. Joint with stainless steel rivet. Extremely smooth action for fatigue-free work. With opening spring and opening limiter. With wire clamp - no uncontrolled jumping away of wire sections. Cutting edge hardness approx. 54 HRC. INOX - tool steel. - Shape: 1 - cutting values medium hard wire (diameter): $\varnothing 1,0$ mm - cutting values soft wire (diameter): $\varnothing 0,2 - 1,6$ mm - jaw length (B): 9mm - jaw thickness (at joint) (D): 7,5mm - head width (A): 13,5mm - ESD: Yes

- Precision pliers for finest cutting work, e.g. in electronics and precision mechanics
- Handles electrically conductive - dissipative
- Ground, very sharp cutting edges without facet
- Shear cut with controlled micro cutting edge offset for long service life and ultra-precise cutting of even the thinnest wires
- Precisely shaped tips also cut adjacent wires from $\varnothing 0.2$ mm
- Joint with stainless steel rivet
- Extremely smooth action for fatigue-free work
- With opening spring and opening limiter

item number	WL19448
model	78 13 125 ESD
manufacturer	KNIPPEX
manufacturer item number	78 13 125 ESD

Products for the electronic industry



length	130 mm
width	61 mm
height	12 mm
length with packaging	189 mm
width with packaging	72 mm
height with packaging	48 mm
Packaging volume	0.637 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	single pack
standards	DIN EN 61 340-5, DIN ISO 9654
product series	Electronic-Super-Knips®
RoHS conform	no
VDE	no
Cut form	without bevel
ESD safe	yes
tool length	125 mm
type of side cutter	side cutter
type of handle	With multi-component sheaths
cutting value wire diameter medium	1 mm
cutting value wire diameter soft	1.6 mm