

ESD electronic side cutter, with bevel, 115 mm



ESD For fine cutting work, e.g. in electronics and precision mechanics. Electrically dissipative handles. Stable, push-through and backlash-free joint. Low-friction double spring for smooth and even opening. Mirror polish in combination with a fine oil film provides good rust protection - no interference in the circuit due to flaking chrome parts. Cutting edges additionally induction hardened, cutting edge hardness approx. 62 HRC. Handles with two-colour multi-component sheaths black/grey. Round head, with facet and wire clamp - no uncontrolled jumping away of wire sections. Cutting edge hardness approx. 62 HRC. - Shape: 1 - Cutting values medium hard wire (diameter): Ø 1,2mm - Cutting values hard wire (diameter): Ø 0,6mm - Cutting values soft wire (diameter): Ø 0,3 - 1,6mm - Jaw length (B): 14mm - Jaw thickness (at joint) (D): 7,5mm - Head width (A): 11mm - ESD: Yes

- For fine cutting work, e.g. in electronics and precision mechanics
- Handles electrically conductive dissipative
- Stable, push-through and backlash-free joint
- Low-friction double spring for smooth and even opening
- Mirror polish in combination with a fine oil film provides good rust protection no interference in the circuit due to flaking chrome parts
- Cutting edges additionally induction hardened, cutting edge hardness approx. 62 HRC
- Handles with two-colour multi-component covers black/grey

| item number | item | number |
|-------------|------|--------|
|-------------|------|--------|

WL19478

Products for the electronic industry





| model | 77 12 115 ESD |
|------------------------------------|-------------------------------|
| manufacturer | KNIPEX |
| manufacturer item number | 77 12 115 ESD |
| length | 115 mm |
| width | 66 mm |
| height | 17 mm |
| length with packaging | 189 mm |
| width with packaging | 72 mm |
| height with packaging | 48 mm |
| Packaging volume | 0.713 dm ³ |
| order unit | 1 piece |
| content unit | 1 piece |
| type of packaging | single pack |
| standards | DIN EN 61 340-5, DIN ISO 9654 |
| RoHS conform | no |
| VDE | no |
| Cut form | large bevel |
| ESD safe | yes |
| tool length | 115 mm |
| type of side cutter | side cutter |
| type of handle | with multi-component handles |
| cutting value wire diameter hard | 0.6 mm |
| cutting value wire diameter medium | 1.2 mm |
| cutting value wire diameter soft | 1.6 mm |
| type of pliers | cutting pliers |
| | |

Products for the electronic industry

