

ESD electronic side cutter, pointed, with small facet, 115 mm



ESD For fine cutting work, e.g. in electronics and precision mechanics. Handles electrically conductive - dissipative. Stable, push-through and backlash-free joint. Low-friction double spring for smooth and even opening. Mirror polish in combination with a fine oil film provides good rust protection - no interference in the circuit due to flaking chrome parts. Cutting edges additionally induction hardened, cutting edge hardness approx. 62 HRC. Handles with two-colour multi-component sheaths black/grey. pointed head, with small facet. Cutting edge hardness approx. 60 HRC. - Shape: 3 - Cutting values medium-hard wire (diameter): Ø 1.0mm - Cutting values hard wire (diameter): Ø 0.5mm - Cutting values soft wire (diameter): Ø 0.3 - 1.3mm - Jaw length (B): 14mm - Jaw thickness (at joint) (D): 7mm - Head width (A): 11mm - ESD: Yes

- For fine cutting work, e.g. in electronics and precision mechanics
- Handles electrically conductive - dissipative
- Stable, push-through and backlash-free joint
- Low-friction double spring for smooth and even opening
- Mirror polish in combination with a fine oil film provides good rust protection - no interference in the circuit due to flaking chrome parts
- Cutting edges additionally induction hardened, cutting edge hardness approx. 62 HRC
- Handles with two-colour multi-component covers black/grey

item number

WL19484

Products for the electronic industry



model	77 32 115 ESD
manufacturer	KNIPEX
manufacturer item number	77 32 115 ESD
GPSR manufacturer information	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
length	117 mm
width	54 mm
height	17 mm
length with packaging	189 mm
width with packaging	71 mm
height with packaging	51 mm
Packaging volume	0.707 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	single pack
standards	DIN EN 61 340-5, DIN ISO 9654
RoHS conform	no
VDE	no
Cut form	small bevel
ESD safe	yes
tool length	115 mm
type of side cutter	side cutter
type of handle	with multi-component handles
cutting value wire diameter hard	0.5 mm
cutting value wire diameter medium	1 mm
cutting value wire diameter soft	1.3 mm
type of pliers	cutting pliers