

ESD Electronic-Super-Knips® , side cutter, fine, glass fiber, 125 mm



Electronic Super Knips® ESD precision pliers for the finest cutting work, e.g. in electronics and precision mechanics. Handles electrically conductive - dissipative. Ground, very sharp cutting edges without facet. Shear cut with controlled micro cutting edge offset for long life and ultra-precise cutting of even the thinnest wires. Precisely shaped tips also cut adjacent wires from \varnothing 0.2 mm. Joint with stainless steel rivet. Extremely smooth action for fatigue-free work. With opening spring and opening limiter. With wire clamp - no uncontrolled jumping away of wire sections. Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC. Special tool steel, burnished. - Shape: 7 - Cutting values medium hard wire (diameter): \varnothing 1,2mm - Cutting values soft wire (diameter): \varnothing 0,2 - 1,6mm - Jaw length (B): 9mm - Jaw thickness (at joint) (D): 7,5mm - Head width (A): 13,5mm - ESD: Yes

- Precision pliers for finest cutting work, e.g. in electronics and precision mechanics
- Handles electrically conductive - dissipative
- Ground, very sharp cutting edges without facet
- Shear cut with controlled micro cutting edge offset for long service life and ultra-precise cutting of even the thinnest wires
- Precisely shaped tips also cut adjacent wires from \varnothing 0.2 mm
- Joint with stainless steel rivet
- Extremely smooth action for fatigue-free work
- With opening spring and opening limiter

item number	WL19495
model	78 71 125 ESD
manufacturer	KNIPEX

manufacturer item number	78 71 125 ESD
GPSR manufacturer information	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
length	130 mm
width	61 mm
height	13 mm
length with packaging	189 mm
width with packaging	72 mm
height with packaging	48 mm
Packaging volume	0.637 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	single pack
standards	DIN EN 61 340-5, DIN ISO 9654
product series	Electronic-Super-Knips®
RoHS conform	no
surface	burnished
VDE	no
Cut form	without bevel
ESD safe	yes
tool length	125 mm
type of side cutter	side cutter
type of handle	With multi-component sheaths
cutting value wire diameter medium	1.2 mm
cutting value wire diameter soft	1.6 mm