

SONOREX SUPER ultrasonic bath 28 litres



SONOREX SUPER baths with 0.9 to 90.0 litres capacity.

The robust and compact SONOREX SUPER ultrasonic baths are characterised by their convenient operability. The size and number of cleaning products or sample vessels determine the selection of the appropriate ultrasonic cleaning bath.

- Internal dimensions of oscillating tank (L x W x D mm): 500 x 300 x 200 mm
- Oscillating systems
- Ultrasonic frequency 35 kHz
- Time setting 1 - 15 min, $\pm 5\%$, continuous operation (∞)
- H-types with adjustable temperature range 30 - 80 °C, RK 31 H with heating 65 °C - fixed setting
- Oscillating tanks made of stainless steel
- RK 102 H with hard-chrome plated oscillating tank, robust stainless steel housing - easy to clean and protected against dripping water
- from RK 102 H the ultrasonic baths have a drain for easy emptying
- Operating voltage 230 V \sim ($\pm 10\%$), alternatively 115 V \sim ($\pm 10\%$), 50/60 Hz
- SONOREX SUPER ... CH ultrasonic baths from 45 to 90 litres capacity offer an even

Products for the electronic industry



longer lifetime due to welded oscillating tank made of stainless steel 1.4404, 2 mm
• SONOREX SUPER ultrasonic baths: medical device class I

Item no.	WL19829
Model	RK 1028
Manufacturer	BANDELIN
Manufacturer article no.	322
GPSR manufacturer data	BANDELIN electronic GmbH & Co. KG Heinrichstrasse 3-4 DE-12207 Berlin www.bandelin.com
Sales unit	1 piece
Content unit	1 piece
Contents (liters)	28 l
Rated power	300 W
Power consumption	1,4 AMPERE
Ultrasonic power (max.)	1200 W