

ESD cross-recess screwdriver Kraftform Micro, PH 0 x 60 mm



Electrostatic-protected micro screwdriver. Reliable protection against electrostatic energy and associated damage. Lightning-fast twirling is possible by resting the hand on the rotating cap and thanks to the fast rotation zone underneath the rotating cap. No more time-consuming regripping. Power zone with integrated soft zones ensures the transmission of high loosening and tightening torques. Precision zone for the correct angle of rotation for adjustment work. The Black Point tip offers a precise fit and optimized corrosion protection. Take it easy tool finder with color coding according to profiles and size stamping - for finding the required tool quickly and easily.

- Application: Phillips-Recess slotted head screws
- Blade: Round
- Finish: Nicromatt, Black Point Lace
- Handle: Kraftform Micro with roll-off protection and rotating cap, multi-component
- Output size: PH 0
- Blade diameter: 3 mm

Item no.	WL21890
Model	1550 PH ESD Kraftform Micro
Manufacturer	WERA
Manufacturer article no.	05030111001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	157 mm
Width	13 mm
Height	13 mm
Length with packaging	174 mm
Width with packaging	64 mm
Height with packaging	34 mm
Scope of delivery	PH 0x60

Products for the electronic industry



Sales unit	1 piece
Content unit	1 piece
VDE	no
Screw type	PH0
ESD compliant	yes
Packaging dimensions	piece
Screwdriver type	normal screwdrivers
Tool length	157 mm
Handle length	97 mm
Blade diameter	3 mm
Blade length	60 mm
Blade length in inches	2.375 in

Other versions

Item no.	Screw type
WL21889	PH00
WL21890	PH0
WL21891	PH1