

ESD extraction arm System 50 Flex 1 joint 700 mm, black - table mounting



The Alsident System 50 Flex is intended for an air volume of 45 - 85 m³/h and has a pipe diameter of 50 mm. The Flex system is particularly suitable for the electronics industry and laboratories. The ESD extraction arm naturally meets the requirements of DIN EN 61340-5-1.

- Increased possibilities of positioning due to the flexible hose
- Suction tip with an elaborately processed cantilever to increase the efficiency of detection
- Maintenance-free O-rings
- Integrated throttle valve, which is in open position from the air flow to ensure maximum air flow
- Threaded rods, springs and thumbscrews in acid-resistant stainless steel (AISI 316L)
- Acid-resistant POP® rivets for increased durability even when used in aggressive environments
- Tested for use in ESD areas According to IEC 61340-5-1:2016

- The earthing cable has a 1 MΩ safety resistor
- All components RoHS compliant.

item number	WL22418
model	50-21-1-23-6
manufacturer	ALSIDENT
manufacturer item number	50-21-1-23-6
order unit	1 piece
content unit	1 piece
colour	black
Colour	black
material	Pipes and suction tip made of chromated aluminium TCP - layer thickness 10μ, hose made of plastic, joints made of conductive polypropylene
product series	Alsident System 50 Flex
number of joints	1
range	700 mm
diameter of tube	50 mm
air volume extraction arm	45 – 85 m ³ /h
assembling	table mounting
joint colour	black
device series	WSA-10LR, WSA-20LR, WSA-5LR
ESD safe	yes