

Suction arm system DN50 Flex for table mounting, 2 joints, red, 900 mm



The Alsident System 50 Flex is intended for an air volume of 45 - 85 m³/h and has a pipe diameter of 50 mm. The Flex system is particularly suitable for the electronics industry and laboratories.

- Increased possibilities of positioning due to the flexible hose
- Suction tip with an elaborately processed cantilever to increase the efficiency of detection
- Maintenance-free O-rings
- Integrated throttle valve which is in open position from the air flow to ensure maximum flow through the unit
- Threaded rods, springs and thumbscrews in acid-resistant stainless steel (AISI 316L)
- Acid-resistant POP® rivets for increased durability even when used in aggressive environments
- All components RoHS compliant.

Item no.	WL22622
Model	50-3721-1-23-4
Manufacturer	ALSIDENT
Manufacturer article no.	50-3721-1-23-4
GPSR manufacturer data	Alsident system A/S Finlandsvej 10 DK-8450 Hammel www.alsident.com
Sales unit	1 piece
Content unit	1 piece
Colour	red
Material	Tubes and suction tip made of anodised aluminium - layer thickness 10μ, plastic hose, polypropylene joints
Incl. battery	no
Product series	Alsident System 50 AL
Number of joints	2
Reach	900 mm
Pipe diameter	50 mm
Air volume of the extraction arm	45 – 85 m ³ /h
Mounting type	table mounting
Joint colour	red
Device series	WSA-10LR, WSA-20LR, WSA-5LR
ESD compliant	no