Extraction arm System 50 Flex 2 joints, 900 mm, red - table mounting



The Alsident System 50 Flex is intended for an air volume of 45 - 85 m3/h and has a pipe diameter of 50 mm. The Flex system is particularly suitable for the electronics industry and laboratories.
• Increased possibilities of positioning due to the flexible hose
• Suction tip with an elaborately processed cantilever to increase the efficiency of detection
• Maintenance-free O-rings
• Integrated throttle valve which is in open position from the air flow to ensure maximum flow through the unit
• Threaded rods, springs and thumbscrews in acid-resistant stainless steel (AISI 316L)
• Acid-resistant POP® rivets for increased durability even when used in aggressive environments
• All components RoHS compliant.

item number	WL22622
model	50-3721-1-23-4
manufacturer	ALSIDENT
manufacturer item number	50-3721-1-23-4
order unit	1 piece
content unit	1 piece
colour	red
Colour	red
material	Tubes and suction tip made of anodised aluminium - layer thickness 10µ, plastic hose, polypropylene joints
product series	Alsident System 50 AL
number of joints	2
range	900 mm
diameter of tube	50 mm
air volume extraction arm	45 – 85 m^3/h
assembling	table mounting
joint colour	red
device series	WSA-10LR, WSA-20LR, WSA-5LR
ESD safe	no