

## N2 soldering iron FM2026-03



Soldering iron for FM202 / FX951 / FX952, with nitrogen feed

Soldering under nitrogen, especially for lead-free solder

- operating display via LED
  - incl. yellow sleeve assembly B2765C and nitrogen guard
  - L = 205 mm, 45 g
  - 24 V - 70 W - ESD safe
  - compatible: soldering tip T13-...+N<sup>2</sup> nozzle B27.../28.../29... / all holders of the FH series / sleeve assemblies B2768C red/B2769C blue
  - Power: 70 W (24 V)
  - Temperature range: 200 to 450 °C
  - Resistance between tip and earth:  $\leq 2 \Omega$
  - Potential between tip and earth: 2 mV
  - Heating element: Composite heating element
  - Cable length: 1.2 m
  - Total length: 205 mm (with T13-D24 tip)
  - Weight: 45 g (with T13-D24 tip and nozzle unit C)
- 
- Scope of delivery:
  - Sleeve
  - Sleeve cover
  - plug connector
  - Retaining clip
  - Instructions for use

Item no.	WL22743
Model	FM-2026
Manufacturer	HAKKO
Manufacturer article no.	FM 2026-03
GPSR manufacturer data	TBK - Technisches Büro Kullik GmbH Industriestrasse 27 DE-56276 Großmaischeid

Products for the electronic industry



[www.kullik.com/](http://www.kullik.com/)

Length	205 mm
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
Power	70 W
Voltage	24 V
Handpiece (type)	soldering iron
Matching tips	T13, T17
Cable length	1.2 m
Matching control unit	FM-202, HAKKO-FM-203-11, HAKKO-FM 204-11, HAKKO-FM 206-17, FX-950, HAKKO-FX-951-N2 and FX-952
ESD compliant	yes

