

800/4 Z Screwdriver bit, slotted, 0.5 x 3.0 mm, 70 mm



With the 800/4 Z screwdriver bit, slotted, 0.5 x 3.0 mm, 70 mm, Wera provides a precisely manufactured solution for slotted screw fastenings at a high quality level. The product is technically impressive for slotted screws. Even with sensitive components, the bit delivers consistently precise results - without compromise.

- for slotted screws
- Tough and tough, for universal use
- 1/4" hexagon drive
- suitable for holder according to DIN ISO 1173-F 6,3

Item no.	WL22853
Model	800/4 Z
Manufacturer	WERA
Manufacturer article no.	05059466001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	70 mm
Width	7 mm
Height	7 mm
Length with packaging	118 mm
Width with packaging	35 mm
Height with packaging	15 mm
Scope of delivery	0.5x3.0x70
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
Bit length	70 mm
VDE	no
Screw type	slot

Products for the electronic industry



ESD compliant	no
Tool length	70 mm
Blade diameter	3 mm
Blade length	70 mm
Blade length in inches	2.75 in
Blade width	3 mm
Blade thickness	0.5 mm

Other versions

Item no.	Blade width	Blade thickness	Bit length
WL51597	3 mm	0.5 mm	50 mm
WL22853	3 mm	0.5 mm	70 mm
WL22854	3.5 mm	0.6 mm	70 mm
WL89760	3.5 mm	0.6 mm	152 mm
WL89752	4 mm	0.5 mm	50 mm
WL71953	4 mm	0.8 mm	50 mm
WL89764	4 mm	0.8 mm	70 mm
WL73439	4 mm	0.8 mm	89 mm
WL89761	4 mm	0.8 mm	152 mm
WL89753	4.5 mm	0.6 mm	50 mm
WL71800	4.5 mm	0.6 mm	89 mm
WL89754	5.5 mm	0.8 mm	50 mm
WL89755	5.5 mm	1 mm	50 mm
WL89765	5.5 mm	1 mm	70 mm
WL19121	5.5 mm	1 mm	89 mm
WL89762	5.5 mm	1 mm	152 mm
WL89756	6 mm	1 mm	50 mm
WL89757	6.5 mm	1.2 mm	50 mm
WL89766	6.5 mm	1.2 mm	70 mm
WL71801	6.5 mm	1.2 mm	89 mm
WL89763	6.5 mm	1.2 mm	152 mm
WL89758	8 mm	1.2 mm	50 mm
WL71802	8 mm	1.2 mm	89 mm

WL89759	8 mm	1.6 mm	50 mm
WL89767	8 mm	1.6 mm	89 mm

