

800/4 Z Screwdriver bit, slotted, 0.6 x 3.5 mm, 70 mm



With the 800/4 Z screwdriver bit, slotted, 0.6 x 3.5 mm, 70 mm, Wera provides a precisely manufactured solution for slotted screw fastenings at a high quality level. A central feature is for slotted screws, which is particularly advantageous in continuous use. Thanks to its manufacturing quality, the bit remains dimensionally stable and reliable even with intensive use.

- for slotted screws
- Tough and tough, for universal use
- 1/4" hexagon drive
- suitable for holder according to DIN ISO 1173-F 6,3

Item no.	WL22854
Model	800/4 Z
Manufacturer	WERA
Manufacturer article no.	05059472001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	70 mm
Width	7 mm
Height	7 mm
Length with packaging	80 mm
Width with packaging	70 mm
Height with packaging	17 mm
Scope of delivery	0.6x3.5x70
Sales unit	1 piece
Content unit	1 piece
Bit length	70 mm
VDE	no
Screw type	slot

ESD compliant	no
Tool length	70 mm
Blade diameter	3.5 mm
Blade length	70 mm
Blade length in inches	2.75 in
Blade width	3.5 mm
Blade thickness	0.6 mm

Other versions

Item no.	Blade width	Blade thickness	Bit length
WL51597	3 mm	0.5 mm	50 mm
WL22853	3 mm	0.5 mm	70 mm
WL22854	3.5 mm	0.6 mm	70 mm
WL89760	3.5 mm	0.6 mm	152 mm
WL89752	4 mm	0.5 mm	50 mm
WL71953	4 mm	0.8 mm	50 mm
WL89764	4 mm	0.8 mm	70 mm
WL73439	4 mm	0.8 mm	89 mm
WL89761	4 mm	0.8 mm	152 mm
WL89753	4.5 mm	0.6 mm	50 mm
WL71800	4.5 mm	0.6 mm	89 mm
WL89754	5.5 mm	0.8 mm	50 mm
WL89755	5.5 mm	1 mm	50 mm
WL89765	5.5 mm	1 mm	70 mm
WL19121	5.5 mm	1 mm	89 mm
WL89762	5.5 mm	1 mm	152 mm
WL89756	6 mm	1 mm	50 mm
WL89757	6.5 mm	1.2 mm	50 mm
WL89766	6.5 mm	1.2 mm	70 mm
WL71801	6.5 mm	1.2 mm	89 mm
WL89763	6.5 mm	1.2 mm	152 mm
WL89758	8 mm	1.2 mm	50 mm
WL71802	8 mm	1.2 mm	89 mm

WL89759	8 mm	1.6 mm	50 mm
WL89767	8 mm	1.6 mm	89 mm

