

## Metal PCB magazine 703.3, 380 x 400 x 563 mm

---



PCB magazines series 700: variable width adjustment by toothed belt by hand

Safety screw

Clamping of the toothed belt by means of a knurled screw prevents accidental adjustment of the movable side wall.

Four precision spindles

for adjusting the movable side wall

Transport lock

A latch is mounted on the front and rear as standard. When lifted, the latch is moved outwards and locks in the upper position. The PCBs can be inserted or removed. When lifted again, the guides are locked.

Toothed belt

By pulling the toothed belt, the web walls are adjusted to the required PCB width.

- for high mechanical + thermal stress
- Model: 703.3
- LP: W = 10-310 mm (adjustable), L max = 387 mm

---

Products for the electronic industry



- Magazine: H x W x D = 563 x 380 x 400 mm
- groove depth 3 mm, with transport lock
- Metal web wall
- width adjustment by toothed belt
- stackable (with stacking knobs) or for turning operation
- Temperature of inserts 200 °C, environment 100 °C

|                          |            |
|--------------------------|------------|
| item number              | WL23101    |
| model                    | 8915703    |
| manufacturer             | CAB        |
| manufacturer item number | 8915703    |
| order unit               | 1 piece    |
| content unit             | 1 piece    |
| temperature max.         | 200 °C     |
| ESD safe                 | no         |
| Series PCB magazines     | Series 700 |
| Material PCB magazine    | metal      |