

Soldering tip tester



- Power consumption 2.6W (100V), 2.9W (110V), 2.6W (120V), 2.7W (220V), 2.8W (230V), 3.0W
- Temperature resolution 1°C
- Temperature measuring range 0 to 700°C
- Temperature accuracy $\pm 3^{\circ}\text{C}$ (300 to 600°C)
- $\pm 5^{\circ}\text{C}$ (other than above) (with alkaline battery)
- Temperature sensor K (CA) thermocouple (between target and sensor)
- Voltage resolution 0.1mV
- Voltage measuring range 0 to 40mV (in steps of 45°)
- Voltage accuracy $\pm$ (5% of reading + 1 digit)
- Resistor resolution 0.1 Ω
- Resistance measuring range 0 to 40 Ω
- Resistance accuracy $\pm$ (5% of reading + 1 digit)
- LCD: 3 1/2 digits
- MAX HOLD: MAX HOLD is displayed at the bottom right of the LCD. (without

condensation)

- Dimensions 200(W)×50(H)×120(D)mm
- Ambient temperature/humidity range: 0 to 40°C, 20 to 90%RH
- Weight 1kg

item number	WL23504
model	FG-101-12
manufacturer	HAKKO
manufacturer item number	FG 101B-20
scope of supply	FG-101 Test device 10 Temperature sensor calibration report other accessories
order unit	1 piece
content unit	1 piece