

WR 3M, 3-channel supply unit, 360 W (400 W)



Rework station with 3 channels

The versatile repair station is specifically tailored to the needs and requirements of professional repairs to latest technology electronic sub-assemblies in industrial production engineering and in the repair and laboratory fields. The WR 3M 3-channel rework station control unit provides 400 watts of power via three independently controlled channels - up to 200 watts for hot air, 120 watts for desoldering and 200 watts for soldering. In addition, the WR 3M rework station offers peripheral control for solder baths and preheating plates. The airflow volume is adjustable between 1-15 l/min, so that the output can be precisely selected according to the application. The large and intuitive LCD display allows easy control of the unit and also shows all relevant functions for all three channels. The WR 3M rework station combines flexibility and versatility in one unit.

- 3 independent channels for simultaneous operation of up to 3 tools
- Automatic tool recognition
- Own vacuum channel for pick-up
- Display: LCD
- IPC compliant: (Tip to ground) Corresponds to IPC-J-001
- equipotential bonding
- WT compatible
- Temperature range: soldering and desoldering iron infinitely variable 50 °C - 550 °C (150 °F - 999 °F)

- Adjustable temperature range is tool-dependent. WP 80 / WP 120: 50 °C-450 °C (150 °F-850 °F), WSP 150: 50 °C-550 °C (150 °F-950 °F), WP 200: 50 °C-550 °C (150 °F-950 °F), WMRT / WMRP: 100 °C-450 °C (200 °F-850 °F), DSX 80 / DXV 80: 50 °C-450 °C (150 °F-850 °F), DSX 120: 50 °C-450 °C (150 °F-850 °F), HAP 200 / HAP 1: 50 °C-550 °C (150 °F-999 °F)
- Overcurrent release: 2 A
- Built-in pump: intermittent operation 30/30 s

item number	WL23628
model	WR 3M
model line	WR 3M
manufacturer	WELLER
manufacturer item number	T0053366699N
GPSR manufacturer information	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller.eu
length	280 mm
width	240 mm
height	103 mm
length in inches	11.02 in
width in inches	9.45 in
height in inches	4.06 in
order unit	1 piece
content unit	1 piece
power	400 W
voltage	230 V
air volume max	15 l/min
temperature range °C	50 – 550 °C
temperature range °F	150 – 999 °F
temperature accuracy °F	±17 °F
temperature stability °C	±2 °C
temperature stability °F	±4 °F
vacuum	0.7 Bar
number of channels	3