

Weller Erem 822N Side Cutter - Oval Head ESD Safe 121 Mm, Full Flush 1.6 Mm EREM Series

This is the most widely used head shape

Fits for all cutting applications where easy access is given

It is robust and size for size offers the highest cutting capacity

Made from ESD-safe material to prevent damage to sensitive components

The Perfect Cut - Strong, sharp and precise, every time

Uncompromising Swiss quality created to be strong and durable Weller Erem® Cutters are designed to be strong, durable and sharp, having the highest precision available.

Manufactured with uncompromising Swiss quality and created for worldwide applications, including electronics assembly and healthcare, Weller Erem Cutters are built to last. The signature high-performance cutters set the industry standard with features that include Weller Erem Magic Spring™ providing over one million consistent, precise and accurate movements, High-Precision Screw Joint, and Maximum Opening Stop Technology. Feel the difference with Weller Erem® – the proven choice. Every time.

1500 Weller Erem pneumatic side cutters are light and precise. Thanks to a selection of different cutting heads they can operate extremely versatile. The cutters are suitable for cutting conventional components, soft metals or small plastic parts. The cutting heads can be interchanged easily.

- This is the standard head shape.
- It is used for all cutting tasks in easily accessible places.
- The solid head allows a high cutting capacity and is characterized by robustness.
- Swiss made

item number	WL23649
model	822N
manufacturer	Weller Erem
manufacturer item number	822N
GPSR manufacturer information	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller.eu
order unit	1 piece
content unit	1 piece
VDE	no

Products for the electronic industry



head width	13.5 mm
Cut form	without bevel
ESD safe	yes
Head thickness	7.2 mm
head length	21 mm
tool length	120 mm
type of side cutter	side cutter
length knife edge	15 mm
cutting length	15 mm
cutting value wire diameter medium	1.2 mm
cutting value wire diameter soft	1.8 mm