

Diagonal cutter, chrome-plated, insulated 160 mm



The indispensable side cutter for versatile use. High-quality material and precise workmanship for a long service life. Precision cutting edges for soft and hard wire. Clean cut on thin Cu-wires, also at the cutting tips. Cutting edges additionally induction hardened, cutting edge hardness approx. 62 HRC. Slim head shape for use in hard-to-reach work areas. with extended cutting edge. with bevel. - Cutting values medium-hard wire (diameter): Ø 3.0mm - Cutting values hard wire (diameter): Ø 2mm - Cutting values soft wire (diameter): Ø 4.0mm - VDE-tested: Yes

- The indispensable side cutter for versatile use
- High-quality material and precise workmanship for a long service life
- Precision cutting for soft and hard wire
- Clean cut on thin Cu-wires, also at the cutting tips
- Cutting edges additionally induction hardened, cutting edge hardness approx. 62 HRC
- Slim head shape for use in hard-to-reach working areas

Item no.	WL23697
Model	70 06 160
Manufacturer	KNIPEX
Manufacturer article no.	70 06 160
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	170 mm
Width	55 mm
Height	20 mm

Products for the electronic industry



Length with packaging	177 mm
Width with packaging	61 mm
Height with packaging	30 mm
Volume with packaging	0.315 dm ³
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Incl. battery	no
Standards	DIN EN 60900, DIN ISO 5749 IEC 60900
RoHS compliant	no
Surface	chrome-plated
VDE	no
ESD compliant	no
Fastening for fall protection	nein
Tool length	160 mm
Type of side cutters	side cutter
Grip (expression)	insulated with multi-component sheaths, VDE-tested
Cutting value wire diameter (hard)	2 mm
Cutting value wire diameter (medium)	3 mm
Cutting value wire diameter (soft)	4 mm

Other versions

Item no.	Tool length	Fastening for fall protection
WL61645	125 mm	nein
WL23702	140 mm	nein
WL61646	160 mm	ja
WL23697	160 mm	nein
WL61647	180 mm	ja
WL61648	180 mm	nein