

Flat-nose pliers with cutting edge (Stork's nose pliers), chrome-plated, insulated, 200 mm



Flat round-nose pliers with cutting edge Elastic tips: dimensionally stable even when twisted. Torsion-tolerant, elastic precision tips. Flat-round, long, pointed jaws. With cutting edges for soft, medium-hard and hard wire. Cutting edges additionally induction hardened, cutting edge hardness approx. 61 HRC. straight jaws. - Cutting value medium-hard wire (diameter): Ø 3.2mm - Cutting value hard wire (diameter): Ø 2.2mm - Jaw thickness (at joint) (T1): 9.5mm - Tip width (E): 3.0mm - Tip thickness (D1): 2.5mm - Jaw length (L3): 73.0mm - Head width (W3): 18mm - Shape: 1 - VDE-tested: Yes

- Torsion-tolerant, elastic precision tips
- Flat-round, long, tapered jaws
- With cutting edges for soft, medium-hard and hard wire
- Cutting edges additionally induction hardened, cutting edge hardness approx. 61 HRC

Item no.	WL23703
Model	26 16 200
Manufacturer	KNIPEX
Manufacturer article no.	26 16 200
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	200 mm
Width	56 mm
Height	19 mm
Length with packaging	211 mm
Width with packaging	66 mm

Products for the electronic industry



Height with packaging	30 mm
Volume with packaging	0.41 dm ³
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Incl. battery	no
Standards	DIN EN 60900, DIN ISO 5745 IEC 60900
RoHS compliant	no
Surface	chrome-plated
VDE	no
ESD compliant	no
Fastening for fall protection	nein
Tool length	200 mm
Grip (expression)	Insulated with multi-component sleeves, VDE-tested
Cutting value wire diameter (hard)	2.2 mm
Cutting value wire diameter (medium)	3.2 mm
Type of pliers	snipe nose pliers

Other versions

Item no.	Fastening for fall protection
WL61412	ja
WL23703	nein