Cobra® high-tech water pump pliers, gray atramentized, wrench size 46 mm, 250 mm



KNIPEX Cobra® adjustment at the touch of a button directly on the workpiece. Fine adjustment for optimum adaptation to different workpiece sizes and hand-friendly handle position. Self-clamping on pipes and nuts: no slipping on the workpiece, effort-saving work. Gripping surfaces with specially hardened teeth, hardness of teeth approx. 61 HRC: permanently secure gripping due to high wear resistance. Through-hole joint: high stability due to double guide. Secure locking of the hinge pin: no unintentional adjustment. Pinch protection prevents crushing injuries. - Setting positions: 25 - Capacity for nuts, width across flats (inches): Ø 2 - Capacity for nuts, width across flats (mm): 46mm - Capacity for pipes (diameter): Ø 50mm

- Adjustment at the touch of a button directly on the workpiece
- Fine adjustment for optimum adaptation to different workpiece sizes and hand-friendly handle position
- Self-clamping on tubes and nuts: no slipping on the workpiece, effort-saving work
- Gripping surfaces with specially hardened teeth, hardness of teeth approx. 61 HRC: permanently secure gripping due to high wear resistance
- Through-hole joint: high stability due to double guidance
- Secure locking of the hinge pin: no unintentional adjustment
- Clamp protection prevents crushing injuries

Item no.	**WL23704**
Model	87 01 250
Manufacturer	KNIPEX
Manufacturer article no.	87 01 250
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	249 mm

Width	44 mm
Height	14 mm
Length with packaging	264 mm
Width with packaging	94 mm
Height with packaging	51 mm
Volume with packaging	1.266 dm^3
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Standards	DIN ISO 8976
Product series	Cobra®
RoHS compliant	no
Surface	grey atramentised
VDE	no
ESD compliant	no
Tool length	250 mm
Setting positions	25
Grip (expression)	covered with anti-slip plastic
Type of pliers	water pump pliers

Other versions

Item no.	Tool length
WL32705	125 mm
WL32704	150 mm
WL32703	180 mm
WL23704	**250 mm**
WL61786	300 mm
WL61787	400 mm
WL61788	560 mm