

Heavy duty side cutter, black atramentized, 160 mm



For the hardest, permanent use. High cutting performance with low effort due to optimum coordination of cutting edge angle and transmission ratio. Precision cutting edges additionally induction hardened, (cutting edge hardness approx. 64 HRC) for all wire types including piano wire. - Shape: 0 - Cutting values medium-hard wire (diameter): Ø 3,4mm - Cutting values hard wire (diameter): Ø 2,5mm - Cutting values piano wire (diameter): Ø 2,0mm

- For the hardest, permanent use
- High cutting performance with low effort due to optimum coordination of cutting edge angle and transmission ratio
- Precision cutting edges additionally induction hardened, (cutting edge hardness approx. 64 HRC) for all wire types including piano wire

Item no.	WL23706
Model	74 01 160
Manufacturer	KNIPEX
Manufacturer article no.	74 01 160
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	165 mm
Width	53 mm
Height	16 mm
Length with packaging	206 mm
Width with packaging	86 mm
Height with packaging	37 mm
Volume with packaging	0.655 dm ³

Products for the electronic industry



Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Standards	DIN ISO 5749
RoHS compliant	no
Surface	black atramentised
VDE	no
ESD compliant	no
Fastening for fall protection	nein
Tool length	160 mm
Type of side cutters	side cutter
Grip (expression)	coated with plastic
Cutting value wire diameter (hard)	2.5 mm
Cutting value wire diameter (medium)	3.4 mm
Cutting value diameter (piano wire)	2 mm

Other versions

Item no.	Tool length
WL61685	140 mm
WL23706	160 mm
WL23715	180 mm
WL23716	200 mm
WL61686	250 mm