

side cutters, 80 series, oval jaws, antistatic, without bevel, 0.1-1 mm



Side cutters with oval jaws, ideal for work on cable harnesses and for assembling printed circuit boards.

Made of high-performance ball bearing steel, burnished. Cutting and jaws computer-ground, thus highest precision and constant quality. Induction hardening of the cutting edges to 63-65 HRC. With plastic handles and opening spring.

- Cutting capacity copper D = 0.1-1 mm
- Version "CO" with antistatic, conductive handle covers.

item number	WL23832
model	8142-CO
manufacturer	LINDSTRÖM
manufacturer item number	8142 CO
length	155 mm
width	100 mm
height	65 mm
order unit	1 piece

Products for the electronic industry



content unit	1 piece
product series	80 series
VDE	no
head width	10 mm
jaw form	oval
Cut form	without bevel
ESD safe	no
Cutting capacity side cutter	0,1 - 1 mm
Cutting edge design	without bevel
Jaw shape	oval
tool length	110 mm
type of side cutter	side cutter
length of jaws	10 mm

## Other versions

item number	Cutting capacity side cutter	Cutting edge design	Jaw shape
WL52706	0,1 - 0,8 mm	without bevel	sharpened to a point
<b>WL23832</b>	<b>0,1 - 1 mm</b>	<b>without bevel</b>	<b>oval</b>
WL52705	0,1 - 1,25 mm	without bevel	oval
WL16021	0,2 - 1,6 mm	with fine bevel	oval
WL23223	0,2 - 1,25 mm	with fine bevel	pointed
WL15998	0,2 - 1,25 mm	with bevel	oval
WL52707	0,3 - 1,6 mm	without bevel	oval
WL16035	0,3 - 2 mm	with fine bevel	oval
WL16038	0,4 - 2 mm	with bevel	oval