ESD spiral cable, 1 MOhm, black, 1.8 m, 10/10 mm push button



The ESD spiral cable from Safeguard is an important component for earthing people in the ESD zone (EPA) to protect electronic devices and components from electrostatic discharge. The leakage resistance is 1 Mohm. The length of the cable of 1.8 meters allows flexible working without restricting freedom of movement. The ESD spiral cable in black has 2x 10 mm press studs. The colouring makes it easy to see the cable at all times and in different lighting conditions.

- 1 MOhm
- 1,8 m
- tested according to BGI 818: 2001

Item no.	**WL24074**
Model	SG-SK-10/10DK-SCH-1800mm-1Mohm
Manufacturer	SAFEGUARD
Manufacturer article no.	SG-SK-10/10DK-SCH-1800MM-1MOHM
GPSR manufacturer data	Weidinger GmbH Hertha-Sponer-Str. 1a DE-82216 Gernlinden
Length	1800 mm
Sales unit	1 piece
Content unit	1 piece

Manufacturer colour information	black
Colour	black
Connection 1	Push button: Ø 10mm
Connection 2	Push button: Ø 10mm
Electrical resistance	1 MΩ
ESD certification according to IEC 61340-5-1	yes
ESD compliant	yes
Certified according to BGI818	yes
Connection	10 / 10 mm press stud

Other versions

Item no.	Length
WL24074	**1800 mm**
WL42068	2400 mm
WL42076	3600 mm