

ESD PCB magazine 703.2, polycarbonate, 380 x 400 x 563 mm



PCB magazines series 700: variable width adjustment by toothed belt by hand

Safety screw

Clamping of the toothed belt by a knurled screw prevents accidental adjustment of the movable side wall.

Four precision spindles

for adjusting the movable side wall

Transport lock

A latch is mounted on the front and rear as standard. When lifted, the latch is moved outwards and locks in the upper position. The PCBs can be inserted or removed. When lifted again, the guides are locked.

Toothed belt

By pulling the toothed belt, the web walls are adjusted to the required PCB width.

• Model: 703.2 (PC)

- LP: W = 10-310 mm (adjustable), L max = 387 mm
- Magazine: H x W x D = 563 x 380 x 400 mm
- groove depth 3 mm, with transport lock
- Plastic web wall
- width adjustment by toothed belt
- stackable (with stacking knobs) or for turning operation
- Temperature of inserts 130 °C, environment 80 °C

Item no.	WL24336
Model	8916703
Manufacturer	CAB
Manufacturer article no.	8916703
GPSR manufacturer data	CAB Produkttechnik Wilhelm-Schickard-Straße 14 DE-76131 Karlsruhe www.cabgmbh.com
Length	380 mm
Width	400 mm
Height	563 mm
Sales unit	1 piece
Content unit	1 piece
Colour	black plastic
Material	Plastic black
Temperature (max.)	130 °C
ESD compliant	yes
PCB magazine series	Series 700
PCB magazine material	plastic