

Soldering tip SxP series, chisel-shaped 30° 1.5 x 12.04 mm



SxP-Solder Tip Cartridges are the standard soldering tip range for the Metcal MFR-1110, MFR-2210 and MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The SFP-series are nominally 390 °C. Metcal recommends the SFP-series for the majority of applications. However, the family also offer a higher temperature series designated SCP, nominally 450 °C, for high temperature and thermally demanding applications. STP-series are nominally 330 °C for light load application. Can be used with leaded and lead-free solder. The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

- for most standard applications

item number

WL24726

model

SFP-CHB15

Products for the electronic industry



| | |
|-------------------------------|--|
| manufacturer | OKI |
| manufacturer item number | SFP-CHB15 |
| GPSR manufacturer information | OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com |
| order unit | 1 piece |
| content unit | 1 piece |
| product series | SxP Series |
| temperature max. | 421 °C |
| Tip series | SxP |
| Soldering tip angle | 30 ° |
| tip length | 12.04 mm |
| tip width | 1.5 mm |
| tip shape | chisel-shaped |
| tip alignment | bent |
| tip temperature | 421 °C |
| suitable handle | MFR-H1-SC |
| ESD safe | no |

Other versions

| item number | temperature max. |
|----------------|------------------|
| WL24726 | 421 °C |
| WL27521 | 471 °C |