Soldering tip SxP series, conically angled 0.4 x 15.21 mm



SxP-Solder Tip Cartridges are the standard soldering tip range for the Metcal MFR-1110, MFR-2210 and MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The SFP-series are nominally 390 ˚C. Metcal recommends the SFP-series for the majority of applications. However, the family also offer a higher temperature series designated SCP, nominally 450 ˚C, for high temperature and thermally demanding applications. STP-series are nominally 330 ˚C for light load application. Can be used with leaded and lead-free solder. The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

• for most standard applications

Item no.	**WL24730**
Model	SFP-CNB04

Manufacturer	OKI
Manufacturer article no.	SFP-CNB04
GPSR manufacturer data	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Sales unit	1 piece
Content unit	1 piece
Product series	SxP Series
Temperature (max.)	421 °C
Tip series	SxP
Tip length	15.21 mm
Tip width	0.4 mm
Soldering tip diameter	0.4 mm
Tip shape	angled, conical
Tip alignment	bent
Tip temperature	421 °C
Matching handpiece	MFR-H1-SC
ESD compliant	no

Other versions

Item no.	Temperature (max.)
WL26700	366 °C
WL24730	**421 °C**
WL26999	471 °C