

Rework tip RxP series tunnel for SOIC-8



RxP-Blade/Quad Solder Tip Cartridges are the rework tips for the Metcal MFR-series soldering systems. The second letter in the part number designates the temperature series. RFP-Cartridges are nominally 390 °C. Metcal recommends the RFP temperature series for most applications. However, there is a higher temperature range designated RCP, nominally 450 °C, for high temperature and thermally demanding applications. Can be used with leaded and lead-free solder. The Metcal SmartHeat®-Technology“ will adjust the power levels during soldering to suit the application.

- for most standard applications
- suitable for MFR-1100 and MFR-2200 series

Item no.	WL24743
Model	RFP-DL2
Manufacturer	OKI

Manufacturer article no.	RFP-DL2
GPSR manufacturer data	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
Product series	RxP Series
Type of tip	Tunnel-Rework Lötpatronen
Tip series	RxP
SMT design	SOIC-8
Tip dimensions	5,18 x 4,23 mm
Tip width	2.29 mm
Tip shape	tunnel
Tip alignment	straight
Matching handpiece	MFR-H1-SC
ESD compliant	no

Other versions

Item no.	SMT design
WL24743	SOIC-8
WL24742	SOIC-14-16
WL27216	SOIC-16