


## Soldering tip SxV series, chisel-shaped 5 x 11.7 mm



SxV-Solder Tips are the standard soldering tip range for the Metcal PS-900/MFR1100, MFR-2210, MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The temperature series SFV are nominally 390 °C. Metcal recommends the SFV-series for the majority of applications. However, the family also offer a higher temperature serie designated SCV, nominally 450 °C, for high temperature and thermally demanding applications. STV-series are nominally 330 °C for light load application. Can be used with leaded and lead-free solder The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

- for most standard applications
- original easily accessible geometry
- suitable for the handpieces of PS and MFR systems

item number	WL24766
model	SFV-CH50AR
manufacturer	OKI
manufacturer item number	SFV-CH50AR
GPSR manufacturer information	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com

order unit	1 piece
content unit	1 piece
product series	SxV Series
temperature max.	421 °C
Tip series	SxV
tip length	11.7 mm
tip width	5 mm
tip shape	chisel-shaped
tip alignment	straight
tip temperature	421 °C
ESD safe	no

## Other versions

item number	temperature max.
WL27832	366 °C
<b>WL24766</b>	<b>421 °C</b>
WL26531	471 °C

