

## Soldering tip SxV series, conical long 1.4 x 15 mm

---



SxV-Solder Tips are the standard soldering tip range for the Metcal PS-900/MFR1100, MFR-2210, MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The temperature series SFV are nominally 390 °C. Metcal recommends the SFV-series for the majority of applications. However, the family also offer a higher temperature serie designated SCV, nominally 450 °C, for high temperature and thermally demanding applications. STV-series are nominally 330 °C for light load application. Can be used with leaded and lead-free solder The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

- for most standard applications
- suitable for the handpieces of PS and MFR systems

item number

WL24781

---

Products for the electronic industry



|                          |            |
|--------------------------|------------|
| model                    | SFV-CNL14  |
| manufacturer             | OKI        |
| manufacturer item number | SFV-CNL14  |
| order unit               | 1 piece    |
| content unit             | 1 piece    |
| product series           | SxV Series |
| temperature max.         | 421 °C     |
| Tip series               | SxV        |
| tip length               | 15 mm      |
| tip width                | 1.4 mm     |
| soldering tip diameter   | 1.4 mm     |
| tip shape                | conical    |
| tip alignment            | straight   |
| tip temperature          | 421 °C     |
| ESD safe                 | no         |

## Other versions

|             |                  |
|-------------|------------------|
| item number | temperature max. |
| WL24781     | 421 °C           |