

ESD torque screwdriver 7440, adjustable, 0.3 - 1.2 Nm



Wera torque screwdriver. Reliable protection against electrostatic energy and associated damage. Variable torque setting with maximum accuracy. Easy setting of the required torque value without special tools. Good readability of the scale value. Rapidaptor quick-change technology for lightning-fast bit changes. Unlimited loosening torque for loosening tight screws. Multi-component Kraftform handle with hard and soft zones for high working speeds and to protect the palm of the hand. Suitable for bits with 1/4" external hexagon drive to DIN ISO 1173-C 6.3 and E 6.3 (ISO 1173).

- Adjustable Kraftform ESD torque screwdriver with Rapidaptor quick-change chuck
- Electrostatic safe tool due to surface resistance of $<10^9$ Ohm
- Multi-component Kraftform Micro handle for fast and ergonomic screwdriving
- With hexagonal roll-off protection to prevent rolling away
- With Rapidaptor quick-change chuck for bits with 1/4" external hex drive
- Socket size: 1/4
- Main scale Measuring range: 0.30-1.2 nm
- Length 155 mm

Item no.	WL24825
Model	Serie 7400 ESD Kraftform
Manufacturer	WERA
Manufacturer article no.	05074730001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	188 mm
Width	52 mm
Height	57 mm

Products for the electronic industry



Length with packaging	188 mm
Width with packaging	52 mm
Height with packaging	57 mm
Scope of delivery	7440 ESD, 0.3-1.2 Nm
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
VDE	no
Screw type	hexagonal
ESD compliant	yes
Packaging dimensions	piece
Screwdriver type	torque screwdriver
Torque	0.3 – 1.2 Nm
Tool length	188 mm