

ESD bubble wrap, pink, dissipative, 300 mm, 150 m roll



SafeGuard dissipative ESD bubble wrap is the ideal choice for the safe shipping of sensitive electronic components. The 2-layer film with a 10 mm bubble diameter offers reliable protection and is easy to seal. With a surface resistance of $R_{pp} < 1 \times 10^{11} \text{ Ohm}$, it meets the requirements of DIN EN 61340 and ROHS directives. The pink material made of dissipative LDPE is recyclable, amine-free and available in a roll of 150000 x 300 mm. The film thickness is $55 \mu\text{m} \pm 10 \%$ and the packaging properties are dissipative to ensure maximum ESD safety. Choose SafeGuard for professional protection of your electronic components during transportation.

- Surface resistance: $R_{pp} < 1 \times 10^{11} \text{ Ohm}$
- Properties: Dissipative LDPE
- Dimple diameter: 10mm
- 2-ply
- Weldable, recyclable, amine-free
- Complies with DIN EN 61340 and ROHS directive

Item no.	WL24844
Model	SG-LPT-ROSA-ABL-55
Manufacturer	SAFEGUARD
Manufacturer article no.	SG-LPT-ROSA-ABL-55-150X300
GPSR manufacturer data	Weidinger GmbH Hertha-Sponer-Str. 1a DE-82216 Gernlinden
Length	150000 mm
Width	300 mm
Sales unit	1 rolls
Content unit	1 rolls
Colour	rose
Incl. battery	no
Film thickness	55µm +/- 10 %
Packaging properties	dissipative
ESD certification according to IEC 61340-5-1:2016	yes
ESD compliant	yes

Other versions

Item no.	Width
WL24844	300 mm
WL24845	500 mm
WL24846	600 mm