

ESD precision electronics side cutter, mini head, 120 mm



ESD handles electrically dissipative - dissipative. Precision pliers for the finest cutting work, e.g. in electronics and precision mechanics. Very precisely ground, sharp cutting edges with very small facets for exact cuts on sensitive electronic components; also without facet for flush cutting. Precision cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC. Approx. 20 % less weight than conventional electronic pliers. Bolted joint with particularly carefully manufactured joint surfaces for uniform, low-friction movement in the entire opening range. Smooth-running double spring for smooth and even opening. Ergonomically optimised multi-component sleeves. Mini head. - Shape: 0 - Cutting values medium hard wire (diameter): Ø 1.0mm - Cutting values hard wire (diameter): Ø 0.6mm - Cutting values soft wire (diameter): Ø 0.2 - 1.4mm - Jaw length (B): 6.5mm - Jaw thickness (at joint) (D): 6.5mm - Head width (A): 9mm - ESD: Yes

- Precision pliers for finest cutting work, e.g. in electronics and precision mechanics
- Very precisely ground, sharp cutting edges with very small facets for exact cuts on sensitive electronic components
- Also without facet for flush cutting
- Precision cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC
- Approx. 20 % less weight than conventional electronic pliers
- Bolted joint with particularly carefully manufactured joint surfaces for uniform, low-friction movement in the entire opening range
- Smooth-running double spring for smooth and even opening
- Ergonomically optimised multi-component sleeves

item number

WL24969

Products for the electronic industry



model	79 02 120 ESD
manufacturer	KNIPEX
manufacturer item number	79 02 120 ESD
length	115 mm
width	69 mm
height	20 mm
length with packaging	189 mm
width with packaging	72 mm
height with packaging	48 mm
Packaging volume	0.637 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	single pack
standards	DIN EN 61 340-5, DIN ISO 9654
RoHS conform	no
surface	burnished
VDE	no
Cut form	without bevel
ESD safe	yes
tool length	120 mm
type of side cutter	side cutter
type of handle	with multi-component sleeves
cutting value wire diameter hard	0.6 mm
cutting value wire diameter medium	1 mm
cutting value wire diameter soft	1.4 mm
type of pliers	cutting pliers

