Desoldering tip DxP series, D: 1.55 / 2.85 mm



DxP-Desolder Tips are the standard desoldering tip range for the Metcal desolder series MFR-1150, MFR-1350, MFR-1351 and MFR-UK5. The second letter in the part number designates the temperature series. The temperature series DFP are nominally 390 ˚C. Metcal recommends the DFP-series for most applications. The Temperature series DCP are nominally 450 ˚C and are recommended for high temperature and thermally demanding applications. Can be used with leaded and lead-free solder. The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

- suitable for ceramics and applications with high thermal requirements
- suitable for desoldering systems MFR-1150, MFR-1350, MFR-1351

Item no.	**WL25297**
Model	DCP-CN6
Manufacturer	OKI

Manufacturer article no.	DCP-CN6
GPSR manufacturer data	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Sales unit	1 piece
Content unit	1 piece
Product series	DxP Series
Temperature (max.)	471 °C
Tip series	DxP
Inner diameter	1.55 mm
Outer diameter	2.85 mm
Tip length	5.54 mm
Tip shape	conical
Tip alignment	straight
Tip temperature	460 °C
Matching handpiece	MFR-HDS
ESD compliant	no

Other versions

Item no.	Inner diameter
WL27284	0.64 mm
WL25296	0.79 mm
WL25295	1.05 mm
WL27568	1.31 mm
WL25297	**1.55 mm**
WL25298	2.44 mm