

## Extraction arm System 50 Flex 2 joints, 900 mm, black - table mounting

---



The Alsident System 50 Flex is intended for an air volume of 45 - 85 m<sup>3</sup>/h and has a pipe diameter of 50 mm. The Flex system is particularly suitable for the electronics industry and laboratories.

- Increased possibilities of positioning due to the flexible hose
- Suction tip with an elaborately processed cantilever to increase the efficiency of detection
- Maintenance-free O-rings
- Integrated throttle valve which is in open position from the air flow to ensure maximum flow through the unit
- Threaded rods, springs and thumbscrews in acid-resistant stainless steel (AISI 316L)
- Acid-resistant POP® rivets for increased durability even when used in aggressive environments
- All components RoHS compliant.

item number	WL25902
model	50-3721-1-23-050
manufacturer	ALSIDENT
manufacturer item number	50-3721-1-23-050
order unit	1 piece
content unit	1 piece
colour	black
Colour	black
material	Tubes and suction tip made of anodised aluminium - layer thickness 10μ, plastic hose, polypropylene joints
product series	Alsident System 50 AL
number of joints	2
range	900 mm
diameter of tube	50 mm
air volume extraction arm	45 – 85 m <sup>3</sup> /h
assembling	table mounting
joint colour	black
ESD safe	no